

Tabla de especificaciones

FD	C	44	4	4	SB	7	0
Product	Input voltage	Frame	No. of inputs	No. of Panelboards	Panelboard type ¹	Panelboard main breaker ²	Monitoring
FD	C=208V	44=2 Door bottom cable exit	1=One	1=One	SB=Sq D bolt-in	3=35kAIC	0=No monitoring
	A=480V	54=3 Door bottom cable w/tie breakers	2=Two	2=Two	SP=Sq D plug-in	6=65kAIC	1=Current monitoring
	F=308V, 50 hz	64=2 Door top cable entry	4=Four	3=Three	GB=GE bolt-in	0=None	6=LDMF
	U=400V, 50 hz	74=3 Door top cable exit w/tie breakers	-	4=Four	GB=GE plug-in	A=Plug-in	7=LDMF w/display
	G=415V, 50 hz	-		5=One w/IG	-	7=ABB	8=LDMF w/SiteScan Interface
	M=380V, 60 hz			6=Two w/IG		9=LDMF w/display & SideScan Interface	
	T=400V, 60 hz			7=Three w/IG		C=Current plus monitoring	
	E=415V, 60 hz			8=Four w/IG		-	

	Width		Depth		Height		Weight	
	in.	cm.	in.	cm.	in.	cm.	lbs.	Kg.
Uncrated	23.5	60	38	97	78.5	199	825	374
Domestic packing	48	122	48	122	83	211	850	385
Export packing	50	127	50	127	85	216	1000	454